

IMPACT
A BETTER FLOOR



LUXURY VINYL TILE

PROSPERITY

2.5 MM

RESPONSIVE 

PROSPERITY

LUXURY VINYL TILE

RESPONSIVE



SIZE: 7.25" x 48"


THICKNESS: 2.5 MM

WEAR LAYER: 22 MIL | 0.55 MM


PIECES: 16 PER CARTON

COVERAGE: 38.66 SQ FT / 3.59 M² / CARTON


INSTALLATION: DRY BACK LVT



7.25" x 48" x 2.5 mm
184.15.00 mm x 1219.2 mm x 2.5 mm
22 MIL / 0.55 mm



16 PCS / CARTON
38.66 SQ.FT / CARTON
3.59 SQ.M / CARTON



50 CARTONS / PALLET

PROSPERITY

LUXURY VINYL TILE



Loose Lay Luxury Vinyl Tiles For Commercial and Light Industry
PUR Polyurethane Reinforcement | Product Standard: ISO 10582

CERTIFICATION & CLASSIFICATION	STANDARD	PROSPERITY
TYPE OF FLOOR COVERING	ISO 10582	LUXURY VINYL TILE
CE CERTIFICATION	EN 14041	YES
CLASSIFICATION	EN ISO 10874	32 / 42

TECHNICAL CHARACTERISTICS	STANDARD	PROSPERITY
TOTAL THICKNESS	EN ISO 2436 (EN 428)	2.5 MM
WEAR LAYER THICKNESS	EN ISO 24340 (EN 429)	0.55 MM 22 MIL
SURFACE TREATMENT	UV TREATED	PUR
MASS PER UNIT AREA	EN ISO 23997 (EN 430)	4.2 KG/M ²
WEAR LAYER BINDER CONTENT	ISO 10582	TYPE I
FORM OF DELIVERY	EN ISO 24342 (EN 427) Planks box	7.25" X 48" 16 PLANKS / CARTON = 38.66 SF 184.15 X 1219.2 MM 16 PLANKS / CARTON = 3.59 M ²

TECHNICAL PERFORMANCE	STANDARD	PROSPERITY
DIMENSIONAL STABILITY	EN ISO 23999 (EN 434)	≤0.10%
REACTION TO FIRE	EN 13501 – 1	CLASS BFL-S1
RESIDUAL INDENTATION	EN ISO 24343-1 (EN 433)	≤ 0.05M
WEAR RESISTANCE	EN 660-1	GROUP T
CASTOR CHAIR	EN ISO 4918 (EN 425)	NO DAMAGE
CURL RESULTANT TO HEAT	EN ISO 23999 (434)	≤ 2MM
LIGHT FASTNESS	EN ISO 105 – B02	≥ 6
RESISTANCE TO STAIN	EN 438	GRADE 5
RESISTANCE TO CHEMICALS	EN ISO 26987 (EN423)	GOOD RESISTANCE
SLIP RESISTANCE	DIN 51130 EN 13893	R10 CLASS DS
ELECTRICAL PROPERTIES	EN 1815 EN 1081	<2KVON CONCRETE R1 > 10 ¹⁰ Ω
THERMAL RESISTANCE	EN ISO 10456	0.07 M2 K/W



ISO 9001
ISO 14001
ISO 18001





LIMITED
RESIDENTIAL
WARRANTY




LIGHT
COMMERCIAL
WARRANTY





EN 14041




LAYER DIAGRAM



FEATURES & BENEFITS



APPLICATIONS



FLOURISH
IMP-FLHK-13

RESPONSIVE 



FLOURISH

IMP-FLHK-13

RESPONSIVE



A

B

C

D

E

F

G

H

D

E



THRIVE

IMP-THCF-14

RESPONSIVE 



THRIVE

IMP-THCF-14

RESPONSIVE



A

B

C

D

E

F

G

H

D

E



SINCERE

IMP-SNSC-15

RESPONSIVE 

SINCERE
IMP-SNSC-15

RESPONSIVE



A

B

C

D

E






F

G

H

D

E



AFFLUENT
IMP-AFCT-16

RESPONSIVE 



AFFLUENT

IMP-AFCT-16

RESPONSIVE



A

B

C

D

E

F

G

H

D

E



VIRTUE

IMP-VRSG-17

RESPONSIVE 

VIRTUE
IMP-VRSG-17

RESPONSIVE



A

B

C

D

E

F

G

H

D

E



FORTUNATE
IMP-FTWRH-18

RESPONSIVE 

FORTUNATE
IMP-FTWRH-18

RESPONSIVE



A

B

C

D

E

F

G

H

D

E



AUSPICIOUS

IMP-AURB-19

RESPONSIVE 



AUSPICIOUS

IMP-AURB-19

RESPONSIVE



A

B

C

D

E


F

G

H

D

E



TRIUMPHANT
IMP-TRCO-20



TRIUMPHANT

IMP-TRCO-20

RESPONSIVE



A

B

C

D

E

F

G

H

D

E

